# Pervasive PSQL v11 SP3 Known Issues General Release – January 2013

#### **Known Issues**

The General Release of Pervasive PSQL v11 SP3 has the following known issues. For a list of fixed defects included in this release, see the History file, available at the Pervasive Web site.

#### **Client Requesters/Communications**

| Tracking<br>Number | Description  |
|--------------------|--|
| 57018              | PCC says incorrectly "Windows 32-bit only" for Embedded spaces setting                           |
| 57586              | When a communication session between client and server is no longer valid status 170 is returned |
| 59491              | Pervasive Auto Reconnect (PARC) does not reconnect when only NetBIOS protocol is set.            |

#### Documentation

| Tracking<br>Number | Description   |
|--------------------|---|
| 58262              | Explanation of how to add ActiveX controls to a Visual Basic project is out of date |

#### 118N

| Tracking<br>Number | Description  |
|--------------------|--|
| 57338              | Fails to bind database with lowercase non-Ascii characters using DTI PvModifyDatabase() function |

#### Installation

| Tracking<br>Number | Description   |
|--------------------|---|
| 55591              | After installation, the Add/Remove Programs "Modify" option displays features that were disabled during install |
| 55692              | PSQL applications and services not registered with Restart<br>Manager on Windows Vista and later systems        |
| 55932              | Under High contrast setting welcome and finish screen text is not readable                                      |
| 56018              | Install not prompting user to uninstall PDAC SDK  |
| 56300              | bdu command line utility is installed by a V10 client32 utility   |
| 56496              | Environment variables for v9 are not cleared on upgrading from v9 to v10  |
| 58042              | Command line repair fails if EclipRCP.cab is not present  |
| 58045              | PSQL uninstall does not check for pending reboots on the system   |
| 58102              | PSQL Server install does not detect previous version custom configured WGE service running                      |
| 58355              | Update install on top of 10.10 is slow on Vista 64 bit  |
| 58420              | Install cancellation rollback result different than reported when invoked after the service is started          |
| 58427              | Custom installation using destination path longer than 128 bytes crashes the MicroKernel on Windows 7           |
| 58626              | Linux x64 client uninstall not deleting/psql/bin folder   |

| Tracking<br>Number | Description continued  |
|--------------------|--|
| 59667              | App Event Log reports ""SideBySide"" errors whenever MFC.DLL/<br>MFCU.DLL are loaded from the PSQL install folder though no<br>functional side effects. This is a Microsoft bug as described in http:/<br>/social.msdn.microsoft.com/forums/en-US/vcgeneral/thread/<br>3b69bdfc-a1cf-4af8-a2cc-d5c7ba362fdb.MFC.DLL and MFCU.DLL<br>are incorrectly manifested with a dependency on<br>'Microsoft.VC80.MFCLOC' version '8.0.50608.0' instead of version<br>'8.0.50727.762', which is the actual version of the MFC locale<br>assemblies that come with VS2005 SP1. |
| 59717              | Uninstall after an upgrade install from v10 leaves behind files  |
| 59869              | Uninstall of Client32 and Client64 leaves two RCP folders in registry  |

#### **MicroKernel Engine**

| Tracking<br>Number | Description   |
|--------------------|---|
| 56059              | Query performance slow with blank data pages  |
| 56363              | Accessing a file using two different symlinks on Windows Vista or Windows 2008 results in status 85 (file locked).  |
|                    | If two applications access a file using two different symlinks, the<br>second open results in status 85 (file locked). For example, if one<br>application opens C:\ProgramData\Pervasive<br>Software\PSQL\Demodata\Class.mkd and another application<br>opens C:\Users\All Users\Pervasive<br>Software\PSQL\Demodata\Class.mkd, the database engine returns<br>status 85. |
|                    | Workaround: Use the same path for each open to access the file.   |
| 58003              | A B_GET_EQUAL operation on the system key (index 125) copies<br>244 bytes of the input key buffer even only 8 bytes were passed in.<br>That does not happen on any other index but 125 (system key).  |
| 58439              | File name is not reported when the system error 604.0.23 (I/O error) is reported  |
| 58686              | Large system transaction hangs the MicroKernel.<br>Workaround: Commit multiple smaller transactions.  |
| 58720              | MKDE opens files read-only when the files are being read by backup software   |
| 58906              | Roll forward on file opened in exclusive mode by client will fail with error 88   |

| Tracking<br>Number | Description continued  |
|--------------------|--|
| 60786              | Record locks not being counted correctly by "Waits on Page and Record Locks" counter in Windows Performance Monitor                  |
| 61173              | File locks not being counted correctly by "Waits on File Locks" counter in Windows Performance Monitor                               |
| 61283              | All remote communications fail if the number of communication threads is set to a number larger than 256.                            |
| 61668              | Random crash of Cache Engine may occur during page refresh.<br>(Escalation 223534) (Expect a fix in SP3 Update 1)                    |
| 61773              | Parallel transactional inserts with locks can result in status code 5<br>on multi-core machine under heavy load. (Escalation 229283) |

#### Services

| Tracking<br>Number | Description  |
|--------------------|--|
| 55946              | Set data path to ~150 chars and Pervasive PSQL services will not start |

#### SQL

| Tracking<br>Number | Description   |
|--------------------|---|
| 54781              | Executing a stored procedure that contains a print statement inside<br>the PCC or any other GUI tool (such as ODBCTest) may cause the<br>tool to hang.  |
|                    | Workaround: Modify the PSQL Relational Engine service property to<br>"allow service to interact with desktop." This option is configurable<br>with the "Log On" pane under the service's "Properties" screen. |
| 55768              | Securing a bound database does not stamp existing files correctly.  |
| 55807              | DROP DATABASE disables user session. Any attempt to switch to another database fails.   |
| 56108              | On Linux, creating a user with a password of length 129 or greater is crashing the engine.  |

| Tracking<br>Number | Description continued  |
|--------------------|--|
| 56111              | A GRANT LOGIN query with a password greater than 128 bytes successfully creates a user/login in a database with v2 metadata (Note that the max. password length in v2 metadata is 128 bytes), but the password is truncated to 128 bytes and stored in X\$User system table. |
| 57076              | Data pulled from cross databases of different encodings is corrupted   |
| 57216              | Database Code Page setting change doesn't take effect until all<br>connections are closed  |
| 57330              | Set owner to a value longer than 24 characters returns an erroneous message  |
| 57345              | SQL Engine not matching index definition to existing Btrieve key   |
| 57362              | When doing ODBC translation for UTF8 database, space padding is not adjusted   |
| 57372              | Relational engine converts I18N Characters to upper case   |
| 57385              | SQLForeignKeys() incorrectly returns HY000 instead of HY009 with invalid use of NULL pointer   |
| 58404              | Create database fails if database deleted then re-created and DDFs exist from previous creation  |
| 58630              | "Record Too Large" error from MS Access 2007 (escalation 183524)   |
| 59543              | Saved views lose user-specified column names   |
| 60361              | Alter tables on one database interferes with select query on another database  |
| 61777              | SQL can have long delay before returning status code 84 on a locked record   |
| 61807              | SELECT * INTO not working across databases. (Expect a fix in SP3<br>Update 1)  |
| 61830              | "General Error" seen if OUTER JOIN uses a CONSTANT column.<br>(Escalation 231167) (Expect a fix in SP3 Update 1)   |
| 61836              | Psp_indexes sometimes reports a field twice. (Escalation 231333)<br>(Expect a fix in SP3 Update 1)   |
| 61837              | Incorrect results returned if query involves temp table and CONCAT<br>of non-string columns (Escalation 230353) (Expect a fix in SP3<br>Update 1)  |

## System Driver

| Tracking<br>Number | Description   |
|--------------------|---|
| 56575              | XIO is not supported in the Microsoft cluster environment |

#### Utilities

| Tracking<br>Number | Description   |
|--------------------|---|
| 54434              | PCC SQL Editor text mode only shows details for one view  |
| 54446              | DDF Builder does not support creating a table definition for a file that uses ISR (International Sort Rules). DDF Builder does not currently provide a warning.                     |
|                    | How to determine if a data file uses ISR:   |
|                    | When a key has one of the ACS flags set, look at the 265 bytes for that ACS.  |
|                    | If the signature byte is 0xAC, then it's a User-defined ACS.<br>If the signature byte is 0xAD, then it's a locale-specific ACS.<br>If the signature byte is 0xAE, then it's an ISR. |
| 54785              | BDU utility fails when the secured database password is longer than 111 characters  |
| 54990              | Some configuration settings in PCC are missing from a virtual network computing (VNC) session.  |
|                    | Workaround: To configure the database engine, use PCC directly on that engine's console or use a remote desktop tool other than VNC   |
| 55321              | PCC grid cannot display tables with numerous fields.  |
|                    | Workaround: Use views or SELECT statements to limit the number of fields displayed in the grid.   |
| 55396              | The PSA functionality "View loaded Pervasive modules" does not<br>list 64-bit Pervasive PSQL components   |
| 55960              | DDF Builder encounters error when operating on files that are held open exclusively by another process.   |
|                    | Workaround: Ensure that the files are not held open exclusively by another process.   |
| 56051              | General failure error while setting the Bound property for a secured database in PCC  |
| 56490              | Cancel does not work on Rebuild GUI Utility   |

| Tracking<br>Number | Description continued   |
|--------------------|---|
| 56633              | DDF Builder should not allow saving a file with more than 119 indexes   |
| 56634              | DDF Builder creates an invalid definition for an overlapping segment file   |
| 56681              | Invoking DDF Builder plug-in details on 64-bit Linux results in internal error                                    |
| 56779              | PCC crashes in FedoraCore8 on Linux when adding a new table.  |
|                    | This is caused by a known bug in Sun's JRE.   |
|                    | Workaround: turn off some features using the following command:   |
|                    | sed -i 's/XINERAMA/FAKEEXTN/g' \$JAVA_HOME/<br>lib/i386/xawt/libmawt.so   |
| 56842              | CNVDDF.exe returns status 357 and will not convert dictionary   |
| 56855              | 'Master' login name does not show in PCC on Linux as it does on Windows   |
| 56857              | One-column select in PCC on Linux results in grid taking the entire space instead of the width of the column data |
| 56878              | COLLATE once specified in PCC is not removed on deletion  |
| 57056              | Create Btrieve File\Key Specification Page isn't scrolling  |
| 57070              | When using DDF Builder in a virtual environment the SQL Index pane is very small or can barely be seen            |
| 57077              | DDF Builder does not show preview values for GUID   |
| 57088              | DDF Builder does not complain when you try to create a definition<br>on a file with 1 multisegmented key          |
| 57093              | Help link for Table Definition Editor throws an error dialog  |
| 57111              | DDF Builder will not import btrieve schema remotely against demodata  |
| 57210              | PCC F10 hot key to Execute All SQL Statements does not work on Linux  |
| 57230              | Can't execute a view right after you create it in PCC   |
| 57255              | Window DDF Builder does not recognize 5x files on remote Linux servers  |

| Tracking<br>Number | Description continued   |
|--------------------|---|
| 57257              | Progress dialog displayed when loading data in the grid has unusable cancel button  |
| 57265              | Remote Window DDF Builder cannot see large file with extension going against linux server   |
| 57271              | Cannot export Btrieve Schema from a remote machine using DDF Builder  |
|                    | Workaround: Export the schema locally.  |
| 57310              | On SuSE 10.1 PCC may abort with message "line4: 5502 Aborted".<br>This is a known system issue with SuSE 10.1 GTK controls.               |
| 57334              | butil @commandfile does not utilize quoted paths correctly  |
| 57335              | DDF Builder prompts multiple times for owner name on tables with<br>owner names during database check even if you cancel the<br>operation |
| 57343              | Problem importing Btrieve schema remotely using DDF Builder   |
| 57390              | Error refreshing grid after adding a row in PCC   |
| 57414              | PCC displays a "20: Session Security Error" when showing properties of a table in a secure database                                       |
| 57418              | User information in monitor from 64-bit Unix authentication servers is garbled  |
| 58150              | PCC GUI allows entering scale higher than precision for numeric data types  |
| 58170              | Minimum State Delay units would be better as seconds as in the manual   |
| 58171              | Range description in bcfg for Minimal State Delay is incorrect  |
| 58173              | Preview of DateTime doesn't show Milliseconds values  |
| 58197              | ORDER specified for triggers execution is ignored   |
| 58237              | Call from clilcadm.exe should start the engine like it did pre latest els changes   |
| 58268              | CLI license administrator can connect to another server without username and password but the GUI cannot                                  |
| 58287              | DDFBuilder log file cannot be displayed on SUSE 11  |

| Tracking<br>Number | Description continued  |
|--------------------|--|
| 58303              | w64clilcadm displays a different message to clilcadm when no loca engine is present (when client64 is installed).        |
| 58341              | PCC does not stop infinite loop resulting from stored procedure execution  |
| 58379              | File types incorrect in PCC Open File dialog   |
| 58493              | Signing information details about DDF Builder plugin display is in English on a Japanese system                          |
| 58524              | DDF Builder does not create a new database with default options o with recommended options when directory is not present |
| 58543              | Setting an encoding crashes PCC  |
| 58545              | XIOStats "Open CSV File" returns English errors on a Japanese system   |
| 58602              | CLI license administrator gives erroneous 7317 error when attempting to deauthorize a product key                        |
| 58611              | DDF Builder CheckTable sees LONGVARCHAR columns as a warning   |
| 58738              | RBLDCLI does not work from client with remote file   |
| 58938              | PCC does not accurately reflect the Supported Protocols setting  |
| 59018              | Pvmdconv utility creates corrupted v2 database when converting v2 database to v2 database if foreign keys are defined.   |
|                    | Workaround: Recreate the SQL tables and database in v2 and ther populate with data.                                      |
| 59092              | PCC incorrectly calculates the allowed length for strings on Linux when PCC Connection Encoding is Automatic             |
| 59131              | Function Executor throws access violation exception on executing reset operation   |
| 59539              | Function Executor Clear Owner returns "Incorrect Owner Name" even though a correct owner name is provided.               |
|                    | Workaround: Open the file with the owner name specified, and ther attempt to clear it.                                   |
| 59852              | DDFBuilder does not display the SQL Tables of Btrieve files that cannot be found   |

| Tracking<br>Number | Description continued   |
|--------------------|---|
| 59952              | SQL View on Edit Table in PCC has CREATE INDEX statements in alphabetical order instead of key order    |
| 59978              | PCC executes query by simply selecting the query tab  |
| 60046              | GUI phone activation utility on Linux takes a long time to time out                                     |
| 60108              | TIMESTAMP & DATETIME value '1900-01-01' displays '0000-00-00<br>00:00:00.000' in PCC                    |
| 60400              | DDFBuilder Check Table returns errors on indexes with collating sequences                               |
| 61546              | If autoincrement field is zero, a rebuild of the files changes it to highest row number + 1             |
| 61587              | PCC does not highlight newer Pervasive SQL keywords, such as PCOMPRESS, DATEPART, SOUNDEX, and so forth |

#### Software Developer's Kit (SDK)

# ActiveX

| Issue Number | Description  |
|--------------|--|
| 52378        | After connecting to and disconnecting from a remote host,<br>VAccess properties still displays table name and selected<br>fields of the previously connected database                            |
| 52379        | DdfPath, Location, and Join buttons cannot be operated from the keyboard   |
| 53342        | The ActiveX controls do not update LONGVARCHAR type fields. They read existing data, but if you change the field and do an update/insert, status returns success, but the field has not changed. |
| 53378        | ActiveX does not support the entire range of BigInt values   |
| 53784        | ActiveX does not support the GUID/UNIQUEIDENTIFIER data type   |
| 53785        | ActiveX does not support the DateTime data type  |

#### ADO.NET

| Issue Number | Description   |
|--------------|---|
| 61746        | "IsLNASP" property in the PsqlCommand is marked public,<br>but should be private  |
| 61747        | Setting the environment variable to trace ADO.NET is not working as stated in the documentation   |
| 61748        | ADO.NET Provider needs to initialize timestamp values<br>unless they are explicitly set by the application  |
| 61848        | ADO.NET Provider SDK 3.5 is not installing ADO.NET<br>Provider templates when .NET CLR 2.0 is unavailable.<br>(Expect a fix after the release candidate.) |

#### Btrieve

| Issue Number | Description   |
|--------------|---|
| 59783        | Different status code returned on Windows and Linux when using URI w/missing '@' char in Btrieve operations         |
| 61616        | Status code 1 results on End Transaction operation when local Version operation is made inside a remote transaction |
| 61808        | Status codes 73, 170, and 171 errors seen when another<br>Btrieve application has a process ID greater than 65536   |

#### DTI

| Issue Number | Description   |
|--------------|---|
| 55423        | PvCopyDatabase() does not work for database with<br>referential integrity (RI), regardless of RI level.<br>PvCopyDatabase API cannot properly copy tables with RI<br>constraints. The copied tables with RI constraints return<br>status 73 on open attempts. |
| 58153        | Enumerated Types in DTO & DTI do not include Numeric even digit flag  |

### DTO

| Issue Number | Description   |
|--------------|---|
| 52546        | DtoSession.Property(dtoAccessRights),<br>DtoSession.Property(dtoConnectionType),<br>DtoLicenseMgr.Licenses collection appear in object browser<br>but are not implemented in this release.                            |
| 52548        | DTO does not have the following DTI functionality:<br>PvGetTableStat(), database flags indicating the Btrieve<br>security policy of the database<br>(P_DBFLAG_DBSEC_AUTHENTICATION,<br>P_DBFLAG_DBSEC_AUTHORIZATION). |
| 58153        | Enumerated Types in DTO & DTI do not include Numeric even digit flag  |

#### JCL

| Tracking<br>Number | Description  |
|--------------------|--|
| 58323              | JCL SDK Package is missing PVIDEODB's dbbackup folder and contents   |
| 61583              | JCL uses the same credentials for DTI and secure databases, which usually fails during a connection and returns status code 20 |

#### JDBC

| Tracking<br>Number | Description   |
|--------------------|---|
| 56564              | An exception is thrown when using JDBC with 64-bit version of JRE   |
| 57926              | ESC 179802: JDBC returns DATE, TIME and TYPESTAMP as java.sql.Types 9, 10, 11 instead of the expected 91, 92 and 93 |

#### OLEDB

| Issue Number | Description   |
|--------------|---|
| 55994        | Pervasive OLEDB Provider does not work with a database under "mixed" mode security. |
|              | Workaround: Use MSDASQL Provider instead.   |
| 58146        | Memory leak running .net application using Pervasive OLEDB.                         |

#### PDAC

| Tracking<br>Number | Description  |
|--------------------|--|
| 48812              | PDAC cannot connect to database if security set for DefaultDB  |
| 57363              | PDAC does not support the BIGINT data type.<br>The BIGINT data type is an 8-byte integer. PDAC maps<br>BIGINT to SQL_DECIMAL and manipulates data as<br>SQL_C_CHAR type. |
| 59437              | PDAC PvTable returns status 12 when listing tables with v2 metadata  |
| 61816              | PDAC for XE3 does not correctly handle BCD for 64-bit integers   |